


ECN NO.	REV	DATE	DESCRIPTION	APP'D
	A0	20120325	drawing release	kevin



主要技术性能	
额定电负荷	DC 30V\0.5A
接触电阻	≤0.03 Ω
绝缘电阻	≥100MΩ
耐 压	AC500V(50Hz)/min
插 拔 力	3-30N
使用温度范围	-30-70
使用寿命	5000次

6	PJ06-8142334-06	右弹片脚	1	磷 铜	0.20T	镀 金
5	PJ06-8142334-05	左弹片脚	1	磷 铜	0.20T	镀 金
4	PJ06-8142334-04	中 脚	1	磷 铜	0.20T	镀 金
3	PJ06-8142334-03	小盖脚	1	磷 铜	0.20T	镀 金
2	PJ06-8142334-02	盖 脚	1	磷 铜	0.20T	镀 金
1	PJ06-8142334-01	基 座	1	PPA		黑 色
序号	产品编号	产品名称	数量	材 料	规 格	处 理

LINEAR	ANGLE	NAME(INTENDED USE) PHONE JACK	东莞市全晟通精密制造有限公司 DONGGUAN QUAN SHENG TONG PRECISION MANUFACTURING CO.LTD			
X. ±0.30	X. ±2°	PART NO.(INTENDED USE) PJ06-8142334				
.X ±0.20	.X ±1°	APPD:	TITLE: CUSTOMER DRAWING PJ06-8142334-6P			
.XX ±0.10	.XX ±0.5°	CHKD:	DWG NO.:			
.XXX ±0.05		DR:	3/9-16			
GENERAL TOLERANCE UNLESS OTHERWISE NOTED				UNITS mm	SCALE N/A	SHEET 1/1
						REV. A0

P.C.B LAYOUT TOP VIEW

